



XA140753N / P5 TARGET



LOCAL SECTION A-A / AXIS GAP SHORTENED

Local scale 0.25:1; rolling elements and interfaces schematic.



FRONT VIEW / Scale 0.05:1

Hole phase and tooth profile schematic.

DIMENSIONS AND LIMITS / mm

Item / nominal	Lower / upper limit
Bore 674	TBC
Outside 862.3	TBC
Envelope H 50	TBC

ROTATIONAL LIMITS / µm MAX.

Characteristic	Limit
P5 radial / axial	TBC

Outer: 28 x Ø18 THRU; PCD Ø800.
Other nominal dimensions: h 43, Li 706.
External gear: module 6, teeth 142, pitch_diameter 852, face_width 43. Teeth shown symbolically.
P5/P4 is the LYDL supply target. TBC items require model-specific limits; internal geometry is not a manufacturing definition.

Open: Inner-ring hole count/type not independently listed; outer na not copied to inner ring.

For higher precision grades or custom bearings, please contact:

sales@luoyangdeeplink.com



Luoyang Deeplink Technology Co.,Ltd.

XA140753N / P5 TARGET

LYDL-0501-P5-C

REV C | 2026-10-16 | UNIT mm | SCALE AS STATED

1 / 1

View series specifications

Contact LYDL